



Specifications: So-Lo & So-Lo with Shower Deck Models

Capacity	1 Adult
Dimensions	So-Lo: 32"W x 59 5/8"L x 18"H So-Lo with Shower Deck: 44"W x 59.5"L x 18"H
Door Swing	Right or Left Hand
Warranty	<p>*Lifetime warranty on door seal – first year parts & labor, remaining years, parts only.</p> <p>*3 year warranty on bathtub, door and latching mechanism- 1 year parts and labor, remaining 2 years parts only.</p> <p>*One year warranty on hydrotherapy components, heated seat, flip seat and latch, and drain components purchased from Safety Bath</p> <p>*Warranty does not cover the installation of your So-Lo bathtub, nor does it cover modifications made to the flip-down seat.</p>
Length	59 5/8" L
Width	So-Lo: 32" So-Lo with Shower Deck: 44"
Height	So-Lo: 18" So-Lo with Shower Deck: 18"
Step in height	4"
Weight	Without Jets: 90 lbs With jets – 110 lbs
Door seal	Extruded silicone rubber gasket
So-Lo Safety Seat	<p>*Measures: 18"W x 30"L</p> <p>*Comes with a factory mounted anchor system and 4 screw caps</p> <p>* Safety Seat can be mounted after the So-Lo is installed</p> <p>*Flip-down handle locks seat in upright position when not in use</p> <p>*Constructed of HDPE High Density Polyethylene</p>
Tub surface	Acrylic - "Kohler" white
Tub construction	Acrylic with fiberglass reinforcement

Hinges	Stainless steel
Drain size	1.5", ABS connection
Drain Location	Right or Left hand drain available
Access panel	Measures: 8" x 8" Located in front on jetted tub only , opposite drain location
Heated Seat	So-Lo with Shower Deck model only * Shower deck measures 12"W x 59 5/8"L * 110/120 V – 15 A GFI outlet required
Power Input	110/120 V – 15 A GFI outlet required for jetted tubs
Piping	PVC flex line
Jets	Option: * 12 Warm Air Jets - 12 chrome jets with one way check valves & built-in purge cycle after tub is completely drained.